

BI-FOLD DOORS ENQUIRY/ORDER FORM

Company:

Account No.

Address:

..... Postcode:

Tel:.....

Fax:.....

Contact Name:

Email:

Requested Delivery Date:

Order Reference:

Signature:

Page of

Quote

Order

Any glazing or part of that glazing, which is between the finished floor level and a height of 800mm requires toughened glass as per BS 6262 Part 4: 1994. Ref Part N Building Regulations 1991.

Additional notes:

.....

.....

Profile

Shield

Dimensions (Excluding extension)

Overall width:

.....

Overall height:

.....

Maximum height: 2300mm

Frame colour

White

Cherrywood

Cherrywood on White

Golden Oak

Golden Oak on White

Mahogany

Mahogany on White

Hardware options

Handles & flag hinges

White Gold

Black Chrome

Sigenia hinge covers

White Brown

Top & bottom track

White Brown

Frame extension

25mm frame extension:

.....

x 2.5 mtr = Qty.

Open in/out

Open in

Open out

Glazing (28mm only)

Toughened clear

Unglazed

U-value

1.2 Energy efficient (A)

2.0 Lower cost spec. (B) (STD)

Sill type (Aluminium only)

Track trim

85mm

150mm

Folding options (When viewed from outside)

| Total number of leaves | Number of leaves folding left | Number of leaves folding right |
|-----------------------------|------------------------------------|-------------------------------------|
| | | |
| For example: 3 | 1 | 2 |
| Total number of door leaves | Number of door leaves opening left | Number of door leaves opening right |

Glazing bead

Chamfered Sculptured

Trickle vent

Required

Trickle vents will be fitted to first & last sash

Any special requirements:

.....

.....

.....

.....

.....

.....

.....

Sketch your design here:

.....

.....

.....

.....

.....

.....

.....